

**TELEDEX**

# DESIGNED WITH THE WORLD IN MIND.



Distributed in Australia and  
Pacific Islands Region by:

***TrendTek***  
AUSTRALIA

**TrendTek Australia Pty Ltd**  
Unit 5, 10 Victoria Avenue  
Castle Hill NSW 2154  
AUSTRALIA

**Tel:** +61 2 9680 7711

**Fax:** +61 2 9680 1211

**Email:** [info@trendtek.com.au](mailto:info@trendtek.com.au)

**Web:** [www.trendtek.com.au](http://www.trendtek.com.au)

## OPAL SERIES

Soft curves, legendary quality.



# INTERNATIONAL DESIGN

The Teledex Opal Series combines stylish international design with legendary Teledex reliability, in a package that helps any property put its best foot forward.

## Opal DCT 1900/2900/1800/2800 Series

- 1.9 and 1.8 GHz DECT Technology for best range, clarity, & security
- Single or Two line configuration
- EZ-Answer connects to incoming call by pressing any key
- Superior Quality Speakerphone for convenient Hands-free calls
- Two lines with conference\*
- Supports up to five handsets, including one on the base and four remotes
- AutoSync – handset automatically syncs with base unit when in cradle
- ExpressNet™ broadband-ready
- Easy-access data port
- Up to ten Configurable Guest Service Keys
- LifeLinePlus allows use during power failure
- Last number redial
- Lighted handset keypad
- Handset page/locator
- Low battery indicator
- Breakage-resistant, non-extending antenna
- Large printable faceplate area
- Line status indicators\*
- Bright message wait lamp and positive charge indicator
- 5-Year Warranty

*\*Two-line only*



## Opal 1000/2000 Series Analog

- Single or Two line configuration
- Optional speakerphone
- Auto Detect MWI for high and low voltage signaling
- Large printable faceplate area for important dialing and contact information
- ExpressNet® broadband-ready
- Easy-access data port for convenient laptop computer connection
- Sleek Euro design complements any room decor
- Extra-bright message waiting indicator
- Electronic 3-way conference\*
- Last-number redial
- Up to 11 Configurable Guest Service Keys
- Handset volume boost
- 5-Year Warranty

*\*Two-line only*



## Opal Trimline Analog Series

- Single or Two line configuration
- Optional message waiting indicator
- ADA-compliant volume control
- Analog data port
- Flash, Redial, Mute keys
- 5-Year Warranty



# OPAL DCT 1900/2900/1800/2800 SERIES

## SPECIFICATIONS

<b>Standard Color:</b>	Ash and Black
<b>Footprint (Desk):</b>	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.13" (5.41cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.38" (8.59cm) (d) (with handset)
<b>Footprint (Wall):</b>	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 1.75" (4.45cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.0" (7.62cm) (d) (with handset)
<b>Footprint (RediDock):</b>	3.75" (w) x 8.17" (l) x 3.38" (d) (9.53cm x 20.75cm x 8.59cm)
<b>Weight:</b>	2.0 lbs. (0.9kg)
<b>Weight (Redidock):</b>	7 oz. (0.2kg) (without handset) 0.95 lbs. (0.43kg) (with handset)
<b>Frequency:</b>	1.9 GHz or 1.8 GHz
<b>Power:</b>	9 VDC adapter
<b>Standby Time:</b>	14 days

## PART NUMBERS

### DECT 1.9 GHZ (SINGLE LINE)

#### Opal DCT1905

OPL95149	Ash
OPL951491	Black

#### Opal DCT1910

OPL95339	Ash
OPL953391	Black

#### RediDock

##### RD1910 (Single-line)

OPL95339HDKIT	Ash
OPL953391HDKIT	Black

### DECT 1.9 GHZ (TWO LINE)

#### Opal DCT2905

OPL97149	Ash
OPL971491	Black

#### Opal DCT2910

OPL97359	Ash
OPL973591	Black

#### RediDock

##### RD2910 (Two-line)

OPL97359HDKIT	Ash
OPL973591HDKIT	Black

<b>Talk Time:</b>	4 hours
<b>Humidity:</b>	65% ± 20%
<b>Temperature:</b>	77°F ± 50° (25°C ± 10°C)
<b>Packaging:</b>	10 per carton
<b>Packaging (RediDock):</b>	20 per carton
<b>Faceplate Size:</b>	Full length
<b>FCC Specifications:</b>	Meet or exceeds Part 15, Subpart J, Class A, Part 68
<b>Safety Standard:</b>	ETL and CE
<b>Operating Voltage:</b>	24 to 56 VDC Non-Polarity
<b>Flash Timing:</b>	600 ms
<b>Ringer Equivalence:</b>	Z (Use only behind PBX)
<b>Handset:</b>	Hearing Aid compatible
<b>Line Cord:</b>	15-foot, 2 RJ45

# OPAL 1000/2000 SERIES ANALOG

## SPECIFICATIONS

<b>Standard Color:</b>	Ash and Black
<b>Footprint (Desk):</b>	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.13" (5.41cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.38" (8.59cm) (d) (with handset)
<b>Footprint (Wall):</b>	6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 1.75" (4.45cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.0" (7.62cm) (d) (with handset)
<b>Weight:</b>	2.0 lbs. (0.9kg)
<b>Humidity:</b>	65% ± 20%
<b>Temperature:</b>	77°F ± 50° (25°C ± 10°C)
<b>Packaging:</b>	10 per carton

## PART NUMBERS

### SINGLE-LINE MODELS

#### Opal 1001 (Basic)

OPL76009	Ash
OPL760091	Black

#### Opal 1000 (Basic)

OPL76309	Ash
OPL763091	Black

#### Opal 1002 (Basic)

OPL76039	Ash
OPL760391	Black

#### Opal 1003 (3-button)

OPL76739	Ash
OPL767391	Black

#### Opal 1005 (5-button)

OPL76139	Ash
OPL761391	Black

#### Opal 1010 (10-button)

OPL76239	Ash
OPL762391	Black

#### Opal 1003s (3-button speaker)

OPL76749	Ash
OPL767491	Black

#### Opal 1005s (5-button speaker)

OPL76149	Ash
OPL761491	Black

#### Opal 1010s (10-button speaker)

OPL76339	Ash
OPL763391	Black

### TWO-LINE MODELS

#### Opal 2006 (6-button)

OPL78039	Ash
OPL780391	Black

#### Opal 2011 (11-button)

OPL78259	Ash
OPL782591	Black

#### Opal 2006s (6-button speaker)

OPL78149	Ash
OPL781491	Black

#### Opal 2011s (11-button speaker)

OPL78359	Ash
OPL783591	Black

<b>Faceplate Size:</b>	Full length
<b>FCC Specifications:</b>	Meet or exceeds Part 15, Subpart J, Class A, Part 68
<b>Safety Standard:</b>	ETL and CE
<b>Operating Voltage:</b>	24 to 56 VDC Non-Polarity
<b>Flash Timing:</b>	600 ms
<b>Ringer Equivalence:</b>	Z (Use only behind PBX)
<b>Registered Connector:</b>	USOC RJ-14
<b>Handset:</b>	Hearing Aid compatible
<b>Handset Cord:</b>	10-foot coil cord
<b>Cords &amp; Line:</b>	15-foot/10-foot coil

# OPAL TRIMLINE ANALOG SERIES

## SPECIFICATIONS

<b>Standard Color:</b>	Ash and Black
<b>Footprint (Desk, Wall):</b>	3.75" (9.53cm) (w) x 8.17" (20.75cm) (l) x 2.0" (5.08cm) (l) (without handset); 3.75" (9.53cm) (w) x 8.17" (20.75cm) (l) x 3.38" (8.59cm) (l) (with handset)
<b>Weight:</b>	0.95 lbs. (0.43kg)
<b>Power:</b>	Line
<b>Humidity:</b>	65% ± 20%
<b>Temperature:</b>	77°F ± 50° (25°C ± 10°C)

## PART NUMBERS

### OPAL TRIMLINE (SINGLE-LINE)

#### NO MWL

OPL69019	Ash
OPL690191	Black

#### With MWL

OPL69119	Ash
OPL691191	Black

### OPAL TRIMLINE 2 (TWO-LINE)

#### NO MWL

OPL69059	Ash
OPL690591	Black

#### With MWL

OPL69159	Ash
OPL691591	Black

<b>Packaging:</b>	20 per carton
<b>FCC Specifications:</b>	Meet or exceeds Part 15, Subpart J, Class A, Part 68
<b>Safety Standard:</b>	ETL and CE
<b>Operating Voltage:</b>	24 to 56 VDC Non-Polarity
<b>Ringer Equivalence:</b>	Z (Use only behind PBX)
<b>Registered Connector:</b>	USOC RJ-14
<b>Handset:</b>	ADA-compliant
<b>Cords &amp; Line:</b>	15-foot/10-foot coil