



move forward

Bittel Trimline Telephone Model 69IP-T3

UNO Mini SIP Speakerphone

Features & Functions

- Comply with SIP protocols
- Two Hi-Speed Port™ Ethernet Ports
- Bittel Unique Power Adaptor or Network Power POE(802.3af)
- Withdrawing Faceplate
- Up to 6 programmable guest service keys
- Two line auto-select and three-way conference
- Large printable faceplate area for branding and dialing instructions
- Compatible with Alcatel-Lucent, Nortel, Cisco, Mitel, AVAYA, NEC, Siemens and other mainstream IP PBX
- Message waiting indicator compatible with all major hospitality PBXs
- EZ Message Light™, Message Waiting Light with retrieval function
- Handset with HAC
- Call waiting
- SPKR and Handset volume three-step adjustable
- Ringer Volume HI/LOW adjustable
- Flash button with Flash time programmable
- Hold, Mute, Redial
- Phone-only model is wall-mountable

Specifications

- Dimensions: 175×112×143(mm)
- Handset cord: 2.7m
- Line cord: 2.0m
- Color: Silver, charcoal option
- Flash time: 80ms,100ms,300ms,600ms optional, standard 600ms
- Message Waiting Light Voltage:
 1. Standard 90~150V DC
 2. Customized various MWL card compatible with PBX: AVAYA, Siemens, Philips, Alcatel, NEC, Nortel, Mitel, Panasonic, etc.
- Operating Voltage: 24V~60V DC
- Box Dimension: 47×44×23(cm)
- Package (set/carton): 8 set/Carton
- Quality Control: ISO9001, ISO 14001 System
- Quality Approval, CCC, FCC, CE, RoHS
- Complies with Part 15 and Part 68 of FCC Rules
- FCC rules: The unit complies with part 15 and part 68 of the FCC rules and regulations



Distributed By

TrendTek
AUSTRALIA

Unit 5, 10 Victoria Avenue
Castle Hill NSW 2154
Australia

Phone: 1300 310 300
+612 9680 7711
Fax: +612 9680 1211
Email to: info@trendtek.com.au
Web site: www.trendtek.com.au