

# MORE THAN JUST A TELEPHONE.



## M SERIES BLUETOOTH

A game-changer in desktop telephony and in-room connectivity.

Distributed By  
TrendTek Australia Pty Ltd

Phone: 1300 310 300, +612 9680 7711  
Fax: +612 9680 1211  
Email to: [info@trendtek.com.au](mailto:info@trendtek.com.au)  
Web site: [www.trendtek.com.au](http://www.trendtek.com.au)

# M SERIES BLUETOOTH

## ANALOG CORDED

M Series Bluetooth analog corded phones keep guests connected via Bluetooth pairing to stream sound and place/receive calls over their own cell network, and charge smart devices. A high performance stereo sound system replaces stand-alone audio playback devices in the room to save space, and empower enhanced guest telephone speakerphone calls and conferencing. Available with 5 or 10 programmable guest service keys, patented OneTouch voice mail retrieval, and a fully integrated plastic silk-screen faceplate module.

### Bluetooth

Pair smart devices to play music and place and receive mobile phone calls through M Series.

### USB Charging

Two high-current USB charging ports support devices up to 2.1 Amp, including most tablets and smartphones.

### Stereo Speaker System

High-fidelity stereo speakers ensure a quality listening experience for the guest.

### OneTouch Voice Mail Retrieval

Automatically engages the phone's speaker and auto-dials voice mail which enables guests to check messages hands-free.

## Bluetooth Data Specifications

- Bluetooth version 2.1 + EDR (Enhanced Data Rate)
- Profile A2DP (Advanced Audio Distribution Profile)
- Class 2 type range of 10 meters using 2.4 GHz frequency band and auto-connect



USB charging ports for phones and tablets.



M Series Bluetooth sound system versus a standard telephone speaker.

## Analog Corded

- Single or two-line speakerphones
- Five (5) and ten (10) configurable guest service keys
- Patented OneTouch voice mail retrieval
- Bluetooth handset pairing
- Stereo Bluetooth for music streaming
- 2 Side USB power ports for device charging (2.1 Amp)
- HAC/VCH (ADA) compliant handset volume boost
- Dual neon/LED message-waiting light
- Electronic three-way conferencing\*
- Available in black (with custom faceplate options)
- Custom color faceplate options (MOQ required)

*\*Two-line only*

## Analog Trimline Corded

- Single or two-line phones
- HAC/VCH (ADA) compliant handset volume boost
- Dual neon/LED message-waiting light
- Available in black (with custom faceplate options)
- Custom color faceplate options (MOQ required)



Matching MTRM Trimline available.

# M SERIES BLUETOOTH

## M SERIES BLUETOOTH FACEPLATES

M Series Bluetooth faceplates will be installed a) by Cetis if it is a production or National Account Program order, or a paid production order, or b) by a Cetis channel partner or customer, if it is an independent faceplate order, or if the partner or customer choose to install faceplates themselves.

**Standard Color—Charcoal:** Lead time 4–6 weeks from the date Cetis receives the completed Faceplate Worksheet.

**Designer Color Options:** MOQ 100 units. Lead time 8 weeks from the date Cetis receives the completed Faceplate Worksheet. Blue. Green. Red. Contact Cetis for specific PMS color values.

**Custom Colors:** MOQ 500 units, 15% spares, 50% down payment with order and \$9.99 up charge per phone. Lead time to be determined at time of order. (Normal lead time is 12 weeks.)

**National Account Package:** Phone Orders of 50 units or more qualify for the National Account Package. For all other customizations price and lead-time will be determined at the time of order.



M100B10

# M SERIES BLUETOOTH ANALOG

## SPECIFICATIONS

**Standard Color:** ..... Black  
**Footprint:** ..... 8.56" (217.55mm) (l) x 3.64" (92.5mm) (h) x 5.8" (147.2mm) (w)  
**Weight:** ..... 3.3 lbs. (1527g)  
**Power Supply Unit:** ... Input: 100–240V; 50/60Hz, 0.6A Max; Output: 5.0V—2.0A  
**Humidity:** ..... 65% ± 20%  
**Temperature:** ..... 77°F ± 50° (25°C ± 10°C)  
**Packaging:** ..... 10 per carton  
**Faceplate Size:** ..... Full length

**FCC Specifications:** .... Meets or exceeds Part 68, FCC Part 15 & UL 1459 Ref.  
**Safety Standard:** ..... UL - 60950-1 2nd edition  
..... ADA/HAC  
**Operating Voltage:** ..... 24 to 56 VDC Non-Polarity  
**Flash Timing:** ..... 600 ms  
**Ringer Equivalence:** ..... Z (Use only behind PBX)  
**Handset Coil-Cord:** ..... 10 ft (3.048m)  
**Line Cord:** ..... RJ14 line cord - 15 ft (4.5m)

## PART NUMBERS

### SINGLE-LINE ANALOG CORDED

**M100B5 - 5 GSK, Bluetooth Pairing, USB Charging**  
MA10S5DB ..... Black  
**M100B10 - 10 GSK, Bluetooth Pairing, USB Charging**  
MA10S10DB ..... Black  
**M100TRM - Trimline**  
MA10NT ..... Black

### TWO-LINE ANALOG CORDED

**M200B5 - 5 GSK, Bluetooth Pairing, USB Charging**  
MA20S5DB ..... Black  
**M200B10 - 10 GSK, Bluetooth Pairing, USB Charging**  
MA20S10DB ..... Black  
**M200TRM - Trimline**  
MA20NT ..... Black

## PACKAGE CONTENTS

- Handset
- Base Unit
- AC Adapter
- 10 foot Handset Coil Cord
- 15-foot, 4-wire RJ-14 Line Cord
- Fixed Plastic Template