

Aristel

ISDN / VoIP / GSM Enable Digital Key Telephone System DV38



SYSTEM PARAMETERS

- Dimension: 425x362x90(mm)
- AC Input: 110~240Vac
- Consumption: 65W
- Battery Time: 3Hrs. @ 24V/6Ahr
- Basic Capacity: 4 CO & 8 Extensions
- Maximum Capacity: 12 CO & 28 Extensions
- TDM Switch.
- Two Wire Cabling.
- Two Direction Wall Mount

SYSTEM HARDWARE FEATURES

- Standard Analogue CO lines and SLT Interfaces
- ISDN BRI/PRI Interface
- GSM Trunk Interface
- VoIP trunk Interface
- FSK/DTMF Caller ID interface
- Voice Mail
- Battery-Backup charger
- Call Detail Record -SMDR.
- Music On Hold -Melody source.
- Door Phone / Door switch interface.
- Cordless phone compatible
- FAX detection
- PC Interface for System Management

SYSTEM SOFTWARE FEATURES

- 1000 Speed dial number storage
- Individual barring level facility
- Clock / Calendar
- Least Cost Routing -LCR/ARS
- External Call Forward
- 3-Way Conference
- Forced Account Code
- ISDN DID
- ISDN DOD
- Auto Attendant –Courtesy Service
- Service Status/Day/Night/Moon/Holiday
- Hot Line
- And more...

Distributed by

TrendTek
AUSTRALIA

TrendTek Australia Pty Ltd
Unit 5, 10 Victoria Avenue
Castle Hills NSW 2154
AUSTRALIA

Tel: +61 2 9680 7711
Fax: +61 2 9680 1211
Email: info@trendtek.com.au
Web: www.trendtek.com.au