

TELEDEX®

SMALL FOOTPRINT.
ELEGANT LINES.



I SERIES

(formerly Teledex iPhone™)

Accept no substitutes.

Distributed By

TrendTek
AUSTRALIA

Unit 5, 10 Victoria Avenue
Castle Hill NSW 2154
Australia

Phone: 1300 310 300
+612 9680 7711
Fax: +612 9680 1211
Email to: info@trendtek.com.au
Web site: www.trendtek.com.au



I Series VoIP

- Single or Two line speakerphones
- VoIP-based protocol; SIP RFC 3261 compliant
- Codecs supported: G711a; G711μ; G729
- Corded Supports 802.1Q VLAN tagging
- 2-port 10/100 ethernet switch
- Supports 802.1Q VLAN tagging
- Supports DHCP or static IP address
- Electronic 3-way conference*; Hold, Mute, Redial keys
- Cordless: Supports up to five handsets, including one on the base and four remotes (RediDock kits); AutoSync – handset automatically syncs with base unit when in cradle
- 5 or 10 Configurable Guest Service Keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Corded: Visual message waiting indicator
- Cordless: Bright message waiting indicator and positive charge indicator

*Two-line only

I Series Cordless Series Analog

- Single or Two line speakerphones
- ExpressNet® broadband-ready
- EasyTouch™ voice mail access
- Electronic 3-way conference*
- Cordless: PrimeLine/RingLine™ automatic line selection*
- 5 or 10 Configurable Guest Service Keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Corded: Flash, Hold, Mute, Conference*, Redial keys; Bright message waiting indicator; Desk or wall mountable

*Two-line only

I Series Trimline Analog

- Single or Two line configuration
- Optional message waiting indicator; Flash, Redial, Mute keys
- ADA-compliant volume control with enhanced Sonica™ hearing aid compatibility
- Analog data port

*Two-line only

I SERIES VoIP

SPECIFICATIONS

| | |
|---|---|
| Standard Color: | Ash and Black |
| Footprint (Desk): | 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.125" (5.40cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.375" (8.57cm) (d) (with handset) |
| Footprint (Wall): | 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.0" (5.08cm) (d) (without handset); 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset) |
| Footprint (RediDock, Cordless) (Desk, Wall): | 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 2.25" (5.72cm) (d) (without handset); 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 3.38" (8.59cm) (d) (with handset) |
| Weight: | 1.8 lbs. (0.81kg) |
| Weight (Redidock, Cordless): | 7 oz. (0.2kg) (without handset); 0.8 lbs. (0.36kg) (with handset) |
| Frequency: | 1.9 GHz or 1.8 GHz |
| Power: | Power over Ethernet (PoE) |
| Standby Time (Cordless): | 14 days |

| | |
|--|---|
| Talk Time (Cordless): | 4 hours |
| Humidity: | 65% ± 20% |
| Temperature: | 77°F ± 50° (25°C ± 10°C) |
| Packaging: | 10 per carton |
| Packaging (RediDock, Cordless): | 20 per carton |
| Faceplate Size: | Full length |
| FCC Specifications: | Meets or exceeds Part 15, Subpart J, Class A, Part 68 |
| Safety Standard: | ETL and CE |
| Operating Voltage: | 24 to 56 VDC Non-Polarity |
| Flash Timing: | 600 ms |
| Ringer Equivalence: | Z (Use only behind PBX) |
| Registered Connector (Corded): | USOC RJ-14 |
| Handset: | Hearing Aid compatible |
| Line Cord (Cordless): | 15-foot, 2 RJ45 |
| Cords & Line (Corded): | 15-foot RJ45/10-foot coil |

PART NUMBERS

SINGLE-LINE VoIP 1.9 GHz CORDLESS

| | |
|---------------------------------------|-------|
| NDC2105s (5-button speaker) | |
| IPN964591P | Ash |
| IPN964591IP | Black |
| NDC2110s (10-button speaker) | |
| IPN965591P | Ash |
| IPN965591IP | Black |
| RediDock 1.9 GHz (Single-line) | |
| IRD9110-POE | |
| IPN965591PHDKIT | Ash |
| IPN965591IPHDKIT | Black |

| | |
|-------------------------------------|-------|
| NDC2210s (10-button speaker) | |
| IPN985591P | Ash |
| IPN985591IP | Black |
| RediDock 1.9 GHz (Two-line) | |
| IRD9210-POE | |
| IPN985591PHDKIT | Ash |
| IPN985591IPHDKIT | Black |

TWO-LINE VoIP 1.9 GHz CORDLESS

| | |
|------------------------------------|-------|
| NDC2205s (5-button speaker) | |
| IPN984591P | Ash |
| IPN984591IP | Black |

| | |
|--|-------|
| SINGLE-LINE VoIP 1.8 GHz CORDLESS | |
| NDC2105S (5-button speaker) | |
| IPN962591P | Ash |
| IPN962591IP | Black |
| NDC2110S (10-button speaker) | |
| IPN963591P | Ash |
| IPN963591IP | Black |

RediDock 1.8 GHz (Single-line)

| | |
|--------------------|-------|
| IRD8110-POE | |
| IPN963591PHDKIT | Ash |
| IPN963591IPHDKIT | Black |

TWO-LINE VoIP 1.8 GHz CORDLESS

| | |
|-------------------------------------|-------|
| NDC2205S (5-button speaker) | |
| IPN982591P | Ash |
| IPN982591IP | Black |
| NDC2210S (10-button speaker) | |
| IPN983591P | Ash |
| IPN983591IP | Black |
| RediDock 1.8 GHz (Two-line) | |
| IRD8210-POE | |
| IPN985391PHDKIT | Ash |
| IPN985391IPHDKIT | Black |

SINGLE-LINE VoIP CORDED

| | |
|------------------------------------|-------|
| ND2105s (5-button speaker) | |
| IPN331491P | Ash |
| IPN331491IP | Black |
| ND2110s (10-button speaker) | |
| IPN3333491P | Ash |
| IPN3333491IP | Black |

TWO-LINE VoIP CORDED

| | |
|------------------------------------|-------|
| ND2205s (5-button speaker) | |
| IPN341491P | Ash |
| IPN341491IP | Black |
| ND2210s (10-button speaker) | |
| IPN343591P | Ash |
| IPN343591IP | Black |



I SERIES TRIMLINE ANALOG

SPECIFICATIONS

Standard Color: Ash and Black
Footprint: 2.75" (w) x 8.25" (l) x 3.38" (d) [6.99cm x 20.96cm x 8.59cm]
Weight: 0.8 lbs. (0.36kg)
Power: Line
Humidity: 65% ± 20%
Temperature: 77°F ± 50° [25°C ± 10°C]
Packaging: 20 per carton

FCC Specifications: Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Ringer Equivalence: Z (Use only behind PBX)
Registered Connector: USOC RJ-14
Handset: Hearing Aid compatible
Cords & Line: 10-foot coil/8 -inch line cord

PART NUMBERS

iPhone Trimline (Single-line)

| AT1101 NO/MW | AT1102 W/MW |
|-----------------------|-----------------------|
| IPN33019 Ash | IPN33119 Ash |
| IPN330191 Black | IPN331191 Black |

iPhone Trimline 2 (Two-line)

| AT1201 NO/MW | AT1202 W/MW |
|-----------------------|-----------------------|
| IPN34059 Ash | IPN34159 Ash |
| IPN340591 Black | IPN341591 Black |

I SERIES ANALOG

SPECIFICATIONS

Standard Color: Ash and Black
Footprint (Desk): 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.125" (5.40cm) (d) (without handset);
..... 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.375" (8.57cm) (d) (with handset)
Footprint (Wall): 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 2.0" (5.08cm) (d) (without handset);
..... 6.0" (15.24cm) (w) x 9.0" (22.86cm) (l) x 3.5" (8.89cm) (d) (with handset)
Footprint (RediDock, Cordless) (Desk, Wall): 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 2.25" (5.72cm) (d) (without handset);
..... 2.75" (6.99cm) (w) x 8.25" (20.96cm) (l) x 3.38" (8.59cm) (d) (with handset)
Weight: 1.8 lbs. (0.81kg)
Weight (Redidock, Cordless): 7 oz. (0.2kg) (without handset)
..... 0.8 lbs. (0.38kg) (with handset)
Frequency (Cordless): 1.9 GHz or 1.8 GHz
Power: Line
(Cordless) 12 VDC adapter

Standby Time (Cordless): 14 days
Talk Time (Cordless): 6 hours
Humidity: 65% ± 20%
Temperature: 77°F ± 50° [25°C ± 10°C]
Packaging: 10 per carton
Packaging (RediDock): 20 per carton
Faceplate Size: Full length
FCC Specifications: Meets or exceeds Part 15, Subpart J, Class A, Part 68
Safety Standard: ETL and CE
Operating Voltage: 24 to 56 VDC Non-Polarity
Flash Timing: 100 ms to 1000 ms
Ringer Equivalence: Z (Use only behind PBX)
Registered Connector (Cordless): USOC RJ-14
Handset: Hearing Aid compatible
Line Cord (Cordless): 15-foot, 1-RJ45 and 1-RJ14
Cords & Line (Cordless): 15-foot/10-foot coil

PART NUMBERS

SINGLE-LINE ANALOG 1.9 GHz

CORDESS

AC9105s (5-button speaker)

IPN96459 Ash
IPN964591 Black

AC9110s (10-button speaker)

IPN96559 Ash
IPN965591 Black

RediDock 1.9 GHz (Single-line)

IRD9110 Intl.

IPN96559HDKIT Ash
IPN965591HDKIT Black

TWO-LINE ANALOG 1.9 GHz CORDESS

AC9205s (5-button speaker)

IPN98459 Ash
IPN984591 Black

AC9210s (10-button speaker)

IPN98559 Ash
IPN985591 Black

RediDock 1.9 GHz (Two-line)

IRD9210 Intl.

IPN98559HDKIT Ash
IPN985591HDKIT Black

SINGLE-LINE ANALOG 1.8 GHz

CORDESS

AC8105s Intl. (5-button speaker)

IPN96259IP Ash
IPN962591IP Black

AC8110s Intl. (10-button speaker)

IPN96359IP Ash
IPN963591IP Black

RediDock 1.8 GHz (Single-line)

IRD8110 Intl.

IPN96359HDKIT Ash
IPN963591HDKIT Black

TWO-LINE ANALOG 1.8 GHz CORDESS

AC8205s Intl. (5-button speaker)

IPN98259IP Ash
IPN982591IP Black

AC8210s Intl. (10-button speaker)

IPN98359IP Ash
IPN983591IP Black

RediDock 1.8 GHz (Single-line)

IRD8210 Intl.

IPN98359HDKIT Ash
IPN983591HDKIT Black

SINGLE-LINE ANALOG CORDED

A101 (Lobby)

IPN33009 Ash
IPN330091 Black

A100 (Basic)

IPN33309 Ash
IPN333091 Black

A102 (Basic)

IPN33039 Ash
IPN330391 Black

A103 (3-button)

IPN33739 Ash
IPN337391 Black

A105 (5-button)

IPN33139 Ash
IPN331391 Black

A110 (10-button)

IPN33239 Ash
IPN332391 Black

A100s (Basic speaker)

IPN33049 Ash
IPN330491 Black

A103s (3-button speaker)

IPN33749 Ash
IPN337491 Black

A105s (5-button speaker)

IPN33149 Ash
IPN331491 Black

A110s (10-button speaker)

IPN33339 Ash
IPN333391 Black

TWO-LINE ANALOG CORDED

A200s (Basic speaker)

IPN34049 Ash
IPN340491 Black

A203s (3-button speaker)

IPN34749 Ash
IPN347491 Black

A205s (5-button speaker)

IPN34149 Ash
IPN341491 Black

A210s (10-button speaker)

IPN34359 Ash
IPN343591 Black